# Havana - Live Edge Wood Flooring

Images are a guide; natural wood varies. Please order a sample.

## OVERVIEW

| | |
|---|---|
| Species | European oak |
| Colour & surface | Smooth finish, natural hard-wax oil |
| Collection | Live Edge Wood Flooring |

## SPECIFICATIONS

| | |
|---|---|
| Thickness | 17mm / 12mm plywood base /5mm oak hardwood layer |
| Length | Random according to layout |
| Widths | Random according to layout |
| Tongue & Groove | 4 sides |
| Micro Bevels | 4 sides (1.5mm) |
| Appropriate installation method | glue down or nailed |
| Underfloor heating | compatible with self-regulating system |

- Engineered European Oak
- To be installed according to specified layout plan

## TECHNICAL DATA

| | |
|---|---|
| Product type | Live edge two layer engineered parquet - QCXE |
| Reaction to fire | EN 14342:2013 Table 1 \| Dfl - s1 |
| Emission of formaldehyde | EN 14342 \| E1 |
| Thermal conductivity (W/m K) | EN 14342:2013 Table 2 \| 0.16 |
| Biological durability | EN 335 \| UC 1 |
| Moisture content | EN 13183 \| 8% ± 2% |

## STAIR SOLUTIONS

Matching stair nosings, treads and risers are made in the same wood and finish as this floor.

### Square edge nosing

A crisp, modern nose that finishes flush with the riser. Edges are lightly bevelled so the line stays sharp but comfortable underfoot.

### Square nosing, softened edge

The same flush square nose with a small rounded edge, softer to the touch and more resistant to knocks on busy stairs.

### Full bullnose

A traditional fully rounded nose that overhangs the riser – the classic choice for Victorian and Georgian staircases.

### Overhang nosing, rounded corners

An overhanging nose with a flat face and gently rounded corners – a lighter, contemporary take on the bullnose.

### Bespoke treads and risers

Solid or engineered treads, risers, landings and stringers made to measure in any of our woods, grades and finishes.

## FLOOR PROFILES & THRESHOLDS

Solid oak profiles made to the exact height of your floor, unfinished or stained to match (colours 001–040).

### Ramp profile

Slopes gently from the wood floor down to a lower floor such as vinyl, tile or a door threshold, so there is no trip edge.

### Flat threshold

A slim flat bar that covers the joint between two floors of the same height – ideal for doorways between rooms.

### T-bar threshold

A T-shaped profile whose stem sits in the expansion gap between two floors of equal height, allowing both floors to move freely.

### Wood to carpet profile

Finishes the edge where wood flooring meets carpet, with a lip that holds the carpet neatly in place.

### L-shape end profile

An L-shaped edge that wraps the end of the floor where it meets a step, a glass door or a lower level.

## INSTALLATION

| | |
|---|---|
| Before fitting | Acclimatise the boards in the room for at least 72 hours. The subfloor must be clean, dry and level; moisture-test screeds before installation. |
| Method | Fully bonded, secret nailed, floating or self-adhesive (universal bond) system, depending on the subfloor. |
| Underfloor heating | Suitable when fully bonded. Floor surface temperature must not exceed 27°C. |
| Guides | Step-by-step installation guides: www.hoffparquet.co.uk/wood-flooring-installation-guides.html |

## CARE & MAINTENANCE

| | |
|---|---|
| Daily | Sweep or vacuum with a soft floor-brush attachment (no rotating brush). Use felt pads under furniture and mats at entrances. |
| Cleaning | Damp mop (well wrung) with a pH-neutral cleaner for oiled and hard-wax oiled floors, such as Hoff Parquet "Floor Care" Wood Floor Cleaner. No steam mops or vinegar. |
| Maintenance | Refresh with a maintenance oil or "Floor Care" Wax Refresher every 8–12 months at home, more often in busy commercial areas. |
| Full guide | www.hoffparquet.co.uk/cleaning-and-maintenance-instructions.html |

## SAMPLES & ORDERING

| | |
|---|---|
| Samples | Available on request – info@hoffparquet.co.uk |
| Quotation | Supply only or supply and installation across Edinburgh, Glasgow, London and the UK. Free quotations and site visits in Edinburgh and the surrounding areas. |
| Trade | Architects, interior designers and developers: ask about our trade programme and complimentary samples. |
| Certification | Timber from FSC® and PEFC™ certified sources, compliant with UK and EU Timber Regulations. |